

## Power cable < 1 kV, for flexible applications Camerakabel CAM-CC-SWB



<b>Application</b>	<b>: Flexible combi cable for use in security systems, such as camera surveillance systems. Suitable for direct burial.</b>
<b>TECHNICAL DATA</b>	<b>: 0100314</b>
<b>Remarks</b>	<b>: 4 flexible cores + 1 x coax 75 Ohm</b>
Dimension	: 4 x 0.75 + 1 x 1.4
Conductor material	: Copper, bare
	: 1
Conductor category	: Class 5 = flexible
Stranding element	: No
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: No
Core identification	: Colour
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: Yes
Model	: Round
Screen over stranding	: None
Flame retardant	: In accordance with EN 60332-1-2
Material outer sheath	: Polyvinyl chloride (PVC)
Colour outer sheath	: Black
Torsion resistant	: No
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: No
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Outer diameter approx.	: 14.2mm
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Max. conductor temperature	: 70°C
Bending radius	: 192mm
Nominal voltage U0	: 500V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Bare
Specification core insulation	: Other



# JOBARCO

Specification material outer sheath	: No
	: Other
Shape of conductor	: Round
	: Round