

## Data and communication cable EQ-flex CKY



**Application** : Used as computer cable and in other data transmission systems. Flexible, twisted pairs, overall braiding.

**TECHNICAL DATA** : TYPE CKY

**Remarks** : Oil resistant according to EN 50290-2-22 (TM54).

Stranding element	: Pairs
Conductor material	: Copper, bare
Conductor category	: Class 5 = flexible
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Colour
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Braiding
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Low smoke (acc. BS EN 61034-2)	: No
Protective sheath	: Polyvinyl chloride (PVC)
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Flame retardant	: In accordance with EN 60332-1-2
Outdoor use permitted	: No
UV resistant	: No
Armouring/reinforcement	: None
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No
	: Round
Oil resistant (acc. EN 60811-404)	: No
Underground installation	: No
	: No
	: No



# JOBARCO

: Yes

: Yes



ProductNr	Dimension	Colour outer sheath	Number of stranding elements	Outer diameter approx. (mm)
1011002	2 x 2 x 0.14	Grey	2	5.4
1011003	3 x 2 x 0.14	Grey	3	5.6
1011004	4 x 2 x 0.14	Grey	4	5.9
1011005	5 x 2 x 0.14	Grey	5	6.4
1011006	6 x 1 x 0.14	Grey	6	7.2
1011008	8 x 2 x 0.14	Grey	8	7.8
1011010	10 x 2 x 0.14	Grey	10	8.7
1011012	12 x 2 x 0.14	Grey	12	9
1011025	25 x 2 x 0.14	Grey	25	12.6
1011102	2 x 2 x 0.25	Grey	2	6.3
1011103	3 x 2 x 0.25	Grey	3	6.7
1011104	4 x 2 x 0.25	Grey	4	7
1011105	5 x 2 x 0.25	Grey	5	8.1
1011106	6 x 2 x 0.25	Grey	6	8.5
1011108	8 x 2 x 0.25	Grey	8	9.7
1011110	10 x 2 x 0.25	Grey	10	10.8
1011112	12 x 2 x 0.25	Grey	12	11.3
1011116	16 x 2 x 0.25	Grey	16	12.7
1011134	2 x 2 x 0.34	Grey	2	7.2
1011303	3 x 2 x 0.34	Grey	3	7.6
1011304	2 x 4 x 0.34	Grey	2	8.2
1011305	5 x 2 x 0.34	Grey	5	8.7
1011306	6 x 2 x 0.34	Grey	6	9.9
1011138	8 x 2 x 0.34	Grey	8	11.3
1011202	2 x 2 x 0.5	Grey	2	7.9
1011203	3 x 2 x 0.5	Grey	3	8.5
1011204	4 x 2 x 0.5	Grey	4	9.1
1011206	3 x 4 x 0.5	Grey	3	10.8
1011208	8 x 2 x 0.5	Grey	8	12.4
1011210	10 x 2 x 0.5	Grey	10	14.5
1011212	12 x 2 x 0.5	Grey	12	14.5
1011401	2 x 2 x 0.75	Blue	2	8.4
1011402	2 x 2 x 0.75	Grey	2	8.4
1011403	3 x 2 x 0.75	Grey	3	9.6
1011404	4 x 2 x 0.75	Grey	4	10.2
1011406	6 x 2 x 0.75	Grey	6	12.1
1011408	8 x 2 x 0.75	Grey	8	14.3
1011412	12 x 2 x 0.75	Grey	12	16
1011425	25 x 2 x 0.75	Grey	25	22.8



# JOBARCO

<b>ProductNr</b>	<b>Dimension</b>	<b>Colour outer sheath</b>	<b>Number of stranding elements</b>	<b>Outer diameter approx. (mm)</b>
1011503	3 x 2 x 1	Grey	3	10.1
1011504	4 x 2 x 1	Grey	4	10.5