

Power cable < 1 kV, for flexible applications EQ-flex LIYYCY-JZ



Application	: Flexible cable, copper braided. Protects against electromagnetic interference.
TECHNICAL DATA	: TYPE LIYYCY-JZ
Remarks	: Oil resistant according to EN 50290-2-22 (TM54).
Conductor material	: Copper, bare
Conductor category	: Class 5 = flexible
Stranding element	: No
Core insulation material	: Polyvinyl chloride (PVC)
Protective conductor	: Yes
Core identification	: Numbers
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: Yes
Model	: Round
Screen over stranding	: Braiding
Material outer sheath	: Polyvinyl chloride (PVC)
Halogen free (acc. EN 60754-1/2)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -5°C to 70°C
Permitted cable outer temperature after assembling without vibration	: -30°C to 70°C
Max. conductor temperature	: 70°C
Nominal voltage U ₀	: 500V
Core protecton	: No
Nominal voltage U	: 500V
Reaction-to-fire class according to EN 13501-6	: Eca
Conductor surface	: Bare
Specification core insulation	: Other
	: No
Specification material outer sheath	: Other
	: Round
Shape of conductor	: Round



JOBARCO

ProductNr	Dimension	Flame retardant	Colour outer sheath	Outer diameter approx. (mm)
1095604	4 x 1.5	No In accordance with EN	Other	9.7
1017620	18 x 1.5	60332-1-2	Grey	21