



Power cable < 1 kV, for flexible applications Flexellent SAN-JB

Application : Highly flexible, halogen free cable with high chemical resistance and a temperature range of -50° up to +110°C. Very suitable for the Food and Beverage industry: tested and approved by Ecolab for resistance to various aggressive cleaning products.

TECHNICAL DATA : TYPE SAN-JB

Remarks : High resistance to UV- and ozon, solvents, hydrolysis, microbes and animal fats. Wear and tear resistant. resistant to sulphuric acid, battery acid, nitric acid and chlorine.

Conductor material	: Copper, tinned
Conductor category	: Class 6 = very flexible
Stranding element	: No
Core insulation material	: Copolymer, thermoplastic
Protective conductor	: Yes
Core identification	: Colour
Suspension element	: None
Inner sheath	: No
Screen over stranding element	: None
Screen	: No
Model	: Round
Screen over stranding	: None
Flame retardant	: No
Material outer sheath	: Copolymer, thermoplastic
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: Yes
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -40°C to 110°C
Permitted cable outer temperature after assembling without vibration	: -50°C to 110°C
Max. conductor temperature	: 110°C
Nominal voltage U ₀	: 300V
Core protecton	: No
Nominal voltage U	: 500V
Conductor surface	: Tinned
Specification core insulation	: Other
	: Yes
Specification material outer sheath	: Other
	: Round
Shape of conductor	: Round



JOBARCO

ProductNr	Dimension	Outer diameter approx. (mm)
0131613	3 x 1.5	8
0131803	3 x 4	11.8
0131914	4 x 10	19.6