



JOBARCO

Power cable < 1 kV, for flexible applications Highflex PRO CC UL



Application	: Suitable for use in cable chain systems. The keen construction makes the cable extremely flexible and applicable in various continuous moving equipment. The cable has a diminutive bend radius which makes it possible to use it in minuscule spaces. With UL approval.
TECHNICAL DATA	: TYPE PRO CC UL
Standards	: UL 21530
Remarks	: Very good petrol and oil resistant. Sea water resistant. Halogen free. Colour jacket is petrol blue.
Conductor material	: Copper, bare
Conductor category	: Class 6 = very flexible
Stranding element	: No
Protective conductor	: Yes
Core identification	: Numbers
Inner sheath	: No
Screen over stranding element	: None
Screen	: No
Model	: Round
Screen over stranding	: None
Flame retardant	: In accordance with EN 60332-1-2
Material outer sheath	: Copolymer, thermoplastic
Colour outer sheath	: Other
Torsion resistant	: No
Halogen free (acc. EN 60754-1/2)	: Yes
Oil resistant (acc. EN 60811-404)	: Yes
Low smoke (acc. BS EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Permitted cable outer temperature during assembling/handling	: -25°C to 90°C
Permitted cable outer temperature after assembling without vibration	: -40°C to 90°C
Max. conductor temperature	: 70°C
Nominal voltage U ₀	: 300V
No. bending cycles	: 3000000
Core protection	: No
Nominal voltage U	: 600V
Conductor surface	: Bare
	: No



JOBARCO

Shape of conductor

: Round

: Round

ProductNr	Dimension	Core insulation material	Outer diameter approx. (mm)	Bending radius (mm)
0169204	7 x 0.5	Polypropylene	7.1	54
0169205	4 x 1.5	Copolymer, thermoplastic	7.5	57