

## Data and communication cable Jobcom ATEX-d RE-2X(ST)Yv-fl



<b>Application</b>	: Instrumentation cable for signalling and control applications in low-voltage installations. Especially suited for ATEX EX-d applications. The cable passes the restricted breathing test in Annex E.1.
<b>TECHNICAL DATA</b>	: TYPE RE-2X(ST)Yv-fl
Standards	: NEN-EN 50288-7
<b>Remarks</b>	: <b>According to NEN standard: without communication core. Cores white and black in pairs. Numbered per pair (white 1, black 1 etc.). UV resistant acc. to UL1581, s.1200. Oil resistant acc. to ICEA S-73-532. Capacitance c/c 1 pair: max. 100 nF/km; 2 pairs and more: max. 75 nF/km. Inductance at 1 kHz: max. 1 mH/km. Printing cable: JOBCOM EX Type 1 E.1.</b>
Conductor Diameter	: 1.3mm
Conductor material	: Copper, bare
Conductor category	: Class 2 = stranded
Core insulation material	: Crosslinked polyethylene (XLPE)
Core identification	: Numbers
Stranding	: Layers
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Foil
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Low smoke (acc. BS EN 61034-2)	: No
Insulation integrity in accordance with IEC 60331	: No
Protective sheath	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: Yes
Permitted cable outer temperature during assembling/handling	: -5°C to 50°C
Permitted cable outer temperature after assembling without vibration	: -25°C to 70°C
Flame retardant	: In accordance with EN 60332-3-24
Circuit integrity	: No
Outdoor use permitted	: Yes



# JOBARCO

UV resistant	: Yes
Armouring/reinforcement	: None
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No
	: Round
Oil resistant (acc. EN 60811-404)	: No
Underground installation	: No
	: No
	: No
	: No
	: Yes



<b>ProductNr</b>	<b>Dimension</b>	<b>Stranding element</b>	<b>Colour outer sheath</b>	<b>Number of stranding elements</b>	<b>Outer diameter approx. (mm)</b>
0190033	1 x 2 x 1.3	Pairs	Black	1	8.5
0190041	1 x 2 x 1.3	Pairs	Blue	1	8.5
0190050	1 x 3 x 1.3	Triple	Black	1	8.9
0190051	1 x 3 x 1.3	Triple	Blue	1	8.9
0190034	2 x 2 x 1.3	Pairs	Black	2	11.7
0190042	2 x 2 x 1.3	Pairs	Blue	2	11.7
0190035	4 x 2 x 1.3	Pairs	Black	4	13.1
0190043	4 x 2 x 1.3	Pairs	Blue	4	13.1