

Power cable < 1 kV, for fixed installations Tempflex SIF/Z



Application	: Flexible, halogen free silicone wire for use in high temperature environments. Silicone is suitable up to 180 degrees temperatures.
TECHNICAL DATA	: 0123601
Remarks	: Silicone wire suitable for voltage rating up to 10 kV.
Dimension	: 1 x 1.5
Number of cores	: 1
Conductor material	: Copper, tinned
Conductor category	: Class 5 = flexible
Core insulation material	: Rubber - silicone rubber (SIR)
Core identification	: Colour
Core colour	: Black
Max. conductor temperature	: 180°C
Protective conductor	: No
Flame retardant	: In accordance with EN 60332-1-2
Screen	: No
Drain wire	: No
Suspension element	: None
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Protective barrier	: None
Oil resistant (acc. EN 60811-404)	: No
Lead sheath	: No
Armouring/reinforcement	: None
Material outer sheath	: Other
Permitted cable outer temperature after assembling without vibration	: -50°C to 180°C
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: Yes
Nominal voltage U	: 10000V
Low smoke (acc. BS EN 61034-2)	: No
Insulation integrity	: No
Outer diameter approx.	: 7.6mm
Nominal voltage U0	: 10000V
Shape of conductor	: Round
Conductor surface	: Tinned
Twisted cores	: No
Specification core insulation	: Rubber - silicone rubber (SIR)



JOBARCO

Specification material outer sheath : Other
: Round
Min. permitted bending radius, stationary application/permanent installation : 38mm
Circuit integrity : None
: No
: No
: No
: No