

## Power cord Jobspiral SP-ASS



### TECHNICAL DATA

: TYPE SP-ASS

Conductor material

: Copper, bare

Connection 1

: Socket outlet with protective contact, right-angled

Nominal voltage

: 300V to 500V

Spiralized cable

: Yes

Protective conductor

: Yes

With cord switch

: No



# JOBARCO

ProductNr	Dimension	Length (m)	Material outer sheath	Temperature resistance (°C)	Colour outer sheath	Oil resistant (acc. EN 60811-404)
0291001	3 x 0.75	0.5	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290001	3 x 0.75	0.5	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290002	3 x 0.75	0.5	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291005	3 x 0.75	0.75	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290007	3 x 0.75	0.75	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290008	3 x 0.75	0.75	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291002	3 x 1	0.5	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290003	3 x 1	0.5	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290004	3 x 1	0.5	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291006	3 x 1	0.75	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290009	3 x 1	0.75	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290010	3 x 1	0.75	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291003	3 x 1.5	0.5	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290005	3 x 1.5	0.5	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290006	3 x 1.5	0.5	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291007	3 x 1.5	0.75	Polyurethane (PUR)	-30°C to 90	Black	Yes
0290011	3 x 1.5	0.75	Polyvinyl chloride (PVC)	-5°C to 70	Black	No
0290012	3 x 1.5	0.75	Polyvinyl chloride (PVC)	-5°C to 70	White	No
0291009	3 x 1.5	1	Polyurethane (PUR)	-30°C to 90	Black	Yes
0291004	3 x 2.5	0.5	Polyurethane (PUR)	-30°C to 90	Black	Yes
0291008	3 x 2.5	0.75	Polyurethane (PUR)	-30°C to 90	Black	Yes