



JOBARCO

Data and communication cable Jobsignal YY-ST 06



Application	: Signal and control cable for use in intercom, telephone and security appliances.
TECHNICAL DATA	: TYPE YY-ST 06
Standards	: KEMA K 102-314
Remarks	: Colour code according to NEN1597. Outer jacket PVCmb.
Stranding element	: Pairs
Conductor Diameter	: 0.6mm
Conductor material	: Copper, bare
Conductor category	: Class 1 = solid
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Colour
Stranding	: Bundle
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Foil
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Low smoke (acc. BS EN 61034-2)	: No
Protective sheath	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Colour outer sheath	: Grey
Permitted cable outer temperature after assembling without vibration	: -20°C to 70°C
Flame retardant	: In accordance with EN 60332-1-2
Circuit integrity	: No
Outdoor use permitted	: No
UV resistant	: No
Armouring/reinforcement	: None
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No



JOBARCO

Oil resistant (acc. EN 60811-404)
Underground installation

: Round
: No
: No
: No
: No
: No
: Yes

ProductNr	Dimension	Number of stranding elements	Outer diameter approx. (mm)
0157204	2 x 2 x 0.6	2	6
0157206	3 x 2 x 0.6	3	7.1
0157208	4 x 2 x 0.6	4	7.5
0157216	8 x 2 x 0.6	8	8.8
0157220	10 x 2 x 0.6	10	9.4