

## Data and communication cable Jobsignal YY-ST



<b>Application</b>	: Signal and control cable for use in intercom, telephone and security appliances.
<b>TECHNICAL DATA</b>	: TYPE YY-ST
Standards	: KEMA K 102-314
<b>Remarks</b>	: Colour code according to NEN1597. Drain wire 0.8mm underneath foil. Outer jacket PVCmb.
Stranding element	: Pairs
Conductor Diameter	: 0.8mm
Conductor material	: Copper, bare
Conductor category	: Class 1 = solid
Core insulation material	: Polyvinyl chloride (PVC)
Core identification	: Colour
Stranding	: Bundle
Material outer sheath	: Polyvinyl chloride (PVC)
Screen over stranding element	: None
Screen over stranding	: Foil
Halogen free (acc. IEC 60754-2)	: No
Longitudinal water blocking	: No
Halogen free (acc. EN 60754-1/2)	: No
Radial water blocking	: No
Low smoke (acc. IEC 61034-2)	: No
Low smoke (acc. BS EN 61034-2)	: No
Protective sheath	: No
Armouring	: No
Oil resistant (acc. IEC 60811-404)	: No
Permitted cable outer temperature after assembling without vibration	: -20°C to 70°C
Flame retardant	: In accordance with EN 60332-1-2
Circuit integrity	: No
Outdoor use permitted	: No
UV resistant	: No
Armouring/reinforcement	: None
Conductor surface	: Bare
	: No
Longitudinal water blocking cable	: No
Radial water blocking cable	: No



# JOBARCO

Oil resistant (acc. EN 60811-404)  
Underground installation

- : Round
- : No
- : No
- : No
- : No
- : No
- : Yes



<b>ProductNr</b>	<b>Dimension</b>	<b>Colour outer sheath</b>	<b>Number of stranding elements</b>	<b>Outer diameter approx. (mm)</b>
0158703	1 x 2 x 0.8	Blue	1	5.2
0158602	1 x 2 x 0.8	Grey	1	5.2
0158702	1 x 2 x 0.8	Red	1	5.2
0158705	2 x 2 x 0.8	Blue	2	6.8
0158604	2 x 2 x 0.8	Grey	2	6.8
0158704	2 x 2 x 0.8	Red	2	6.8
0158606	3 x 2 x 0.8	Grey	3	7.5
0158709	4 x 2 x 0.8	Blue	4	8.2
0158608	4 x 2 x 0.8	Grey	4	8.2
0158610	5 x 2 x 0.8	Grey	5	9
0158612	6 x 2 x 0.8	Grey	6	9.6
0158616	8 x 2 x 0.8	Grey	8	10.2
0158624	12 x 2 x 0.8	Grey	12	12.3