

UL - STYLE TABLE

Style	Temp. °C	Material	Voltage	AWG range
-------	----------	----------	---------	-----------

Single Core:

1007	80	PVC	300	32 - 16
1011	80	PVC	600	28 - 3
1015	105	PVC	600	28 - 9
1148	60	PVC	600	26 - 16
1149	60	PVC	600	26 - 16
1160	60	PVC	300	26 - 16
1162	60	PVC	600	8
1207	90	PVC	600	28
1498	80	PVC	600	26 - 9
1499	90	PVC	600	26 - 9
1729	80	PVC	300	26 - 16
10012	80/90/105	PVC	0,6/1 kV	30 - 3
10042	80	TPE-E	300	26 - 2
10053	80	PVC	300	26 - 10
10108	90	TPE-E	300	26 - 10
10258	90	TPE-E	0,6/1 kV	26 - 2
10467	80	PP	300	36 - 16
10479	90	TPE-E	300	32 - 10
10615	80	FRPE	600	26 - 3

Multi core:

2448	60	PVC	30	min. 40
2463	80	PVC	600	min. 40
2464	80	PVC	300	*
2490	60	PVC	*	min. 36
2493	60	PVC	*	30 - 16
2550	90	PVC	600	min. 40
2570	80	PVC	600	min. 40
2587	90	PVC	600	min. 40
2653	90	PVC	600	min. 44
20195	75	PVC	300/500	0,75 – 4 mm ²
20234	80	PUR	0,6/1 kV	26 - 2
20235	80	PUR	*	min. 36
20403	60	PVC	300	28 - 16
20870	80	PUR	300	*
20911	80	PUR	300	min. 36
21387	90	TPE	1 kV	min. 26
21529	90	TPE	300	min. 26
21530	90	TPE	600	min. 26

* = not specified